



## EWE STOP® Rust (Liquid)

### TECHNICAL DATA SHEET

**Product Description:** EWE STOP® Rust (Liquid) is a natural coating to protect, maintain and restore metal products. It is supplied as a non-aqueous, semi-viscous liquid, which will combat corrosion and aid lubrication when applied to any metal surface.

It is produced using the naturally protective properties of sheep's wool. EWE STOP® Rust is a penetrating liquid that will protect your metal surfaces from the environment, increasing the product's lifespan.

This product is suitable for internal & external use.

**Suggested Application:** Clean the surface by removing loose materials and organic growth before applying. The surface should be dry before applying the product. Applying EWE STOP® Rust to wet or damp surfaces is not recommended.

It should be shaken thoroughly and applied neat (without dilution) by a low-pressure sprayer.

Apply to a small test area to check you are satisfied with the finish before proceeding to the entire application.

Simply wash spray equipment (and other materials used to apply the product) with warm, soapy water before reuse.

**Features & Benefits:** Provides a hydrophobic, water-resistant coating using the protective properties of sheep's wool. It can be applied even when temperatures are below freezing. VOC-free and non-toxic, making it safe for areas where there are children, pets and wildlife.

**Storage & Handling:** EWE STOP® Rust is packed in recyclable containers. Materials should be stored in a closed container and protected from extreme temperatures. For those with wool allergies, gloves are recommended when handling the product.

**Typical Properties:** Physical properties are listed below (these indicate typical values and are not intended to be used as product specifications):

Coverage: Up to 15m<sup>2</sup> per litre

Appearance at 25°C: Clear to yellow liquid

Odour: Mild, pleasant

Application temperature: -2°C to 30°C

The information contained herein is believed to be reliable. Still, no representations, guarantees or warranties of any kind are made regarding its accuracy, suitability for particular applications, or the results to be obtained. The information is often based on laboratory work with small-scale equipment and does not necessarily indicate end-product performance or reproducibility. The formulations presented may not have been tested for stability and should be used only as a suggested starting point. Because of the variations in methods, conditions and equipment used commercially

in processing these materials, no warranties or guarantees are made as to the suitability of the product for the applications disclosed. Full-scale testing and end-product performance are the responsibility of the user. CaplinTec Limited shall not be liable, and the customer assumes all risk and liability for any use or handling of any material beyond CaplinTec Limited's direct control. The SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, or inducement to practice any patented invention without the patent owner's consent.

© 2023 CaplinTec Limited - Registered in England & Wales, Company Number: 14838716  
Unit 2, OptIC Technology Centre, Ffordd William Morgan, St Asaph, Denbighshire, LL17 0JD