



EWE COAT[®] Shed & Fence Paint (Water-Based)

TECHNICAL DATA SHEET

Product Description: EWE COAT[®] Shed & Fence Paint is a revolutionary, water-based, single-coat, natural wood coating. It is produced from seaweed, plants, timber waste and sheep's wool. Formulated to protect, maintain and restore timber products.

It is supplied as a paint and can be applied by brush, roller or low-pressure sprayer.

Available in 5 Colours: Charcoal, Slate, Terracotta, Olive, Seaweed.

Suggested Application: Clean the surface and remove any dirt or loose organic material before applying. The surface should be dry before applying the product. Applying EWE COAT[®] to wet or damp surfaces is not recommended.

Stir thoroughly. Apply to a small test area to check you are satisfied with the finish before proceeding to the entire application.

Allow 2 hours for drying in normal weather conditions.

This product is enriched with sheep's wool to repel water.

Do not apply in temperatures below 5°C, damp conditions, or if rain is likely before the product dries.

Please note that the tub's colour may be different from the final shade when dry.

Where a strong colour change is required, more coats may be required.

If using more than one tin, mixing them together in a single container before application is advisable.

Simply wash application equipment (and other materials used to apply the product) with warm, soapy water before reuse.

Features & Benefits: Provides a hydrophobic, water-resistant coating to timber using the protective properties of sheep's wool. It is VOC-free and non-toxic, making it safe for the user and for areas where there are children, pets and wildlife.

Storage & Handling: EWE COAT[®] is packed in recyclable containers. Materials should be stored in a closed container and protected from extreme temperatures. For those with wool allergies, gloves are recommended when handling the product.

Typical Properties: Physical properties are listed below (these indicate typical values and are not intended to be used as product specifications):

Coverage: Up to 6m² per litre

Drying Time: 2 Hours

Odour: Mild, pleasant

Application temperature:

5°C to 30°C

The information contained herein is believed to be reliable. Still, no representations, guarantees or warranties of any kind are made regarding its accuracy, suitability for particular applications, or the results to be obtained. The information is often based on laboratory work with small-scale equipment and does not necessarily indicate end-product performance or reproducibility. The formulations presented may not have been tested for stability and should be used only as a suggested starting point. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the product for the applications disclosed. Full-scale testing and end-product performance are the responsibility of the user. CaplinTec Limited shall not be liable, and the customer assumes all risk and liability for any use or handling of any material beyond CaplinTec Limited's direct control. The SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, or inducement to practice any patented invention without the patent owner's consent.

© 2023 CaplinTec Limited - Registered in England & Wales, Company Number: 14838716
Unit 2, OpTIC Technology Centre, Ffordd William Morgan, St Asaph, Denbighshire, LL17 0JD